

Safety Data Sheet

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

Material Name : Jet A-1
Recommended Use / Restrictions of Use : Fuel for aviation turbine engines fitted to aircraft.

Supplier : Shell Eastern Trading (PTE) Ltd

9 North Buona Vista Drive,
#07-01,
Tower 1, The Metropolis
Singapore 138588
Singapore

Telephone : +65-6384 8000
Emergency Telephone Number : +44 (0) 151 350 4595

2. HAZARDS IDENTIFICATION

GHS Classification : Flammable liquids, Category 3
Skin corrosion/irritation, Category 2
Aspiration hazard, Category 1
Specific target organ toxicity - single exposure, Category 3,
Narcotic effects.
Hazardous to the aquatic environment - Long-term Hazard,
Category 2
Acute hazards to the aquatic environment, Category 2

GHS Label Elements Symbol(s) :



Signal Words : Danger

Hazard Statement : PHYSICAL HAZARDS:
H226: Flammable liquid and vapour.

HEALTH HAZARDS:
H315: Causes skin irritation.
H336: May cause drowsiness or dizziness.

Safety Data Sheet

H304: May be fatal if swallowed and enters airways.

ENVIRONMENTAL HAZARDS:

H401: Toxic to aquatic life.

H411: Toxic to aquatic life with long lasting effects.

GHS Precautionary Statements

Prevention : P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P260: Do not breathe dust/fume/gas/mist/vapours/spray.
P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response : P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P331: Do NOT induce vomiting.

Disposal: : P501: Dispose of contents and container to appropriate waste site or reclaimer in accordance with local and national regulations.

Other Hazards which do not result in classification : Slightly irritating to respiratory system.

Liquid evaporates quickly and can ignite leading to a flash fire, or an explosion in a confined space.

Vapour in the headspace of tanks and containers may ignite and explode at temperatures exceeding auto-ignition temperature, where vapour concentrations are within the flammability range.

This material is a static accumulator. Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.

May ignite on surfaces at temperatures above auto-ignition temperature.

Additional Information : This product is intended for use in closed systems only.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture Description : Complex mixture of hydrocarbons consisting of paraffins, cycloparaffins, aromatic and olefinic hydrocarbons with carbon numbers predominantly in the C9 to C16 range. May also

Safety Data Sheet

contain several additives at <0.1% v/v each.

Classification of components according to GHS

Chemical Identity	Synonyms	CAS	Hazard Class (category)	Hazard Statement	Conc.
Kerosine (petroleum), hydrodesulphurised	Kerosine (petroleum), hydrodesulphurised	64742-81-0	Flam. Liq., 3; Skin Corr., 2; STOT SE, 3; Asp. Tox., 1; Aquatic Chronic, 2; Aquatic Acute, 2;	H226; H315; H336; H304; H411; H401;	0.00 - 100.00 %
Kerosine	Kerosine	8008-20-6	Flam. Liq., 3; Skin Corr., 2; STOT SE, 3; Asp. Tox., 1; Aquatic Chronic, 2; Aquatic Acute, 2;	H226; H315; H336; H304; H411; H401;	0.00 - 100.00 %
Kerosine (Fischer Tropsch), Full range, C8-C16 branched and linear alkanes	Kerosine (Fischer Tropsch), Full range, C8-C16 branched and linear alkanes	848301-66-6	Asp. Tox., 1; Flam. Liq., 3;	H304; H226;	0.00 - 50.00 %

Additional Information : Total aromatic hydrocarbons present are typically in the range of 10-20%v/v.

Refer to Ch 16 for full text of H phrases.

Contains Ethylbenzene, CAS # 100-41-4. Contains Xylene (Mixed Isomers), CAS # 1330-20-7. Contains Tri-methylbenzene (all isomers), CAS# 25551-13-7. Contains Cumene, CAS# 98-82-8 Contains Naphthalene, CAS # 91-20-3.

4. FIRST-AID MEASURES

Inhalation : Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.

Skin Contact : Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by

Safety Data Sheet

- washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment. When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop.
- Eye Contact** : Flush eyes with water while holding eyelids open. Rest eyes for 30 minutes. If redness, burning, blurred vision, or swelling persist transport to the nearest medical facility for additional treatment.
- Ingestion** : If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing. Give nothing by mouth.
- Most Important Symptoms/Effects, Acute & Delayed** : If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever. The onset of respiratory symptoms may be delayed for several hours after exposure. Skin irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blisters. Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death.
- Immediate medical attention, special treatment** : Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Clear fire area of all non-emergency personnel.

- Specific hazards arising from Chemicals** : Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Oxides of sulphur. Unidentified organic and inorganic compounds. Carbon monoxide may be evolved if incomplete combustion occurs. Will float and can be reignited on surface water. Flammable vapours may be present even at temperatures below the flash point. The vapour is heavier than air, spreads along the ground and distant ignition is possible.
- Suitable Extinguishing** : Foam, water spray or fog. Dry chemical powder, carbon

Safety Data Sheet

- Media** : dioxide, sand or earth may be used for small fires only.
- Unsuitable Extinguishing Media** : Do not use direct water jets on the burning product as they could cause a steam explosion and spread of the fire. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.
- Protective Equipment & Precautions for Fire Fighters** : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).
- Additional Advice** : Keep adjacent containers cool by spraying with water. If possible remove containers from the danger zone. If the fire cannot be extinguished the only course of action is to evacuate immediately. Contain residual material at affected sites to prevent material from entering drains (sewers), ditches, and waterways.

6. ACCIDENTAL RELEASE MEASURES

Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. See Chapter 13 for information on disposal. Observe the relevant local and international regulations. Evacuate the area of all non-essential personnel. Ventilate contaminated area thoroughly.

- Personal Precautions, Protective Equipment and Emergency Procedures** : May ignite on surfaces at temperatures above auto-ignition temperature. Do not breathe fumes, vapour. Do not operate electrical equipment. Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area and evacuate all personnel. Attempt to disperse the gas or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Monitor area with combustible gas meter.
- Environmental Precautions** : Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers. Take measures to minimise the effects on groundwater. Contain residual material at affected sites to prevent material from entering drains (sewers), ditches, and waterways.
- Methods and Material for Containment and Cleaning Up** : Take precautionary measures against static discharges. For small liquid spills (< 1 drum), transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove

Safety Data Sheet

- contaminated soil and dispose of safely. For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. Shovel into a suitable clearly marked container for disposal or reclamation in accordance with local regulations.
- Additional Advice** : Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. Local authorities should be advised if significant spillages cannot be contained. Maritime spillages should be dealt with using a Shipboard Oil Pollution Emergency Plan (SOPEP), as required by MARPOL Annex 1 Regulation 26.

7. HANDLING AND STORAGE

- General Precautions** : Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material. Air-dry contaminated clothing in a well-ventilated area before laundering. Contaminated leather articles including shoes cannot be decontaminated and should be destroyed to prevent reuse. Prevent spillages. Never siphon by mouth. Maintenance and Fuelling Activities - Avoid inhalation of vapours and contact with skin.
- Precautions for Safe Handling** : Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks. Avoid inhaling vapour and/or mists. Avoid prolonged or repeated contact with skin. When using do not eat or drink. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Earth all equipment. Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
- Conditions for Safe Storage** : Drum and small container storage: Drums should be stacked to a maximum of 3 high. Use properly labelled and closeable containers. Take suitable precautions when opening sealed

Safety Data Sheet

containers, as pressure can build up during storage. Tank storage: Tanks must be specifically designed for use with this product. Bulk storage tanks should be diked (bunded). Locate tanks away from heat and other sources of ignition. The vapour is heavier than air. Beware of accumulation in pits and confined spaces. Electrostatic charges will be generated during pumping. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk. The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable. Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

Product Transfer

: Avoid splash filling. Wait 2 minutes after tank filling (for tanks such as those on road tanker vehicles) before opening hatches or manholes. Wait 30 minutes after tank filling (for large storage tanks) before opening hatches or manholes. Keep containers closed when not in use. Conditions, such as filling empty Filter Water Separator vessels, that lead to the formation of hydrocarbon mists are also particularly hazardous. Contamination resulting from product transfer may give rise to light hydrocarbon vapour in the headspace of tanks that have previously contained gasoline. This vapour may explode if there is a source of ignition. Partly filled containers present a greater hazard than those that are full, therefore handling, transfer and sampling activities need special care. Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge e.g. spark formation. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/s until fill pipe submerged to twice its diameter, then ≤ 7 m/s). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations.

Recommended Materials

: For containers, or container linings use carbon steel and low alloy steel. Aluminium may also be used for applications where it does not present an unnecessary fire hazard. For container linings the following may also be used: Unplasticized

Safety Data Sheet

- polyvinyl chloride (U-PVC), Fluoropolymers (PTFE), Polyvinylidene fluoride (PVDF), Polyetheretherketone (PEEK), Polyamide (PA-11). For seals and gaskets use: Fluoroelastomer (FKM), Viton A, and Viton B, Nitrile butadiene (NBR), Buna-N. For coating (paint) materials use: High build, amine adduct-cured epoxy.
- Unsuitable Materials** : For containers or container linings, examples of materials to avoid are: Polyethylene (PE, HDPE), Polypropylene (PP), Polymethyl methacrylate (PMMA), Acrylonitrile butadiene styrene (ABS). For seals and gaskets, examples of materials to avoid are: Natural rubber (NR), Ethylene Propylene (EPDM), Polychloroprene (CR) - Neoprene, Butyl (IIR), Chlorosulphonated polyethylene (CSM), e.g. Hypalon.
- Container Advice** : Containers, even those that have been emptied, can contain explosive vapours. Do not cut, drill, grind, weld or perform similar operations on or near containers.
- Other Advice** : In the interests of air safety, aviation fuels are subject to strict quality requirements and product integrity is of paramount importance. For one source of information on international standards for the quality assurance of aviation fuels, see www.jointinspectiongroup.org. Ensure that all local regulations regarding handling and storage facilities are followed. See additional references that provide safe handling practices: CENELEC CLC/TR 50404 (Electrostatics – Code of practice for the avoidance of hazards due to static electricity).

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

If the American Conference of Governmental Industrial Hygienists (ACGIH) value is provided on this document, it is provided for information only.

Occupational Exposure Limits

Material	Source	Type	ppm	mg/m3	Notation
Kerosine (petroleum), hydrodesulphurised	ACGIH	TWA(Non-aerosol.)		200 mg/m3	P: Application restricted to conditions in which there are negligible aerosol exposures.as total hydrocarbon vapor

Safety Data Sheet

	ACGIH	SKIN_DES(Non-aerosol.)			Can be absorbed through the skin.as total hydrocarbon vapor
Kerosine	ACGIH	TWA(Non-aerosol.)		200 mg/m3	P: Application restricted to conditions in which there are negligible aerosol exposures.as total hydrocarbon vapor
	ACGIH	SKIN_DES(Non-aerosol.)			Can be absorbed through the skin.as total hydrocarbon vapor
Ethylbenzene	ACGIH	TWA	20 ppm		
	SG OEL	TWA	100 ppm	434 mg/m3	
	SG OEL	STEL	125 ppm	543 mg/m3	
Xylene	ACGIH	TWA	100 ppm		
	ACGIH	STEL	150 ppm		
	SG OEL	TWA	100 ppm	434 mg/m3	
	SG OEL	STEL	150 ppm	651 mg/m3	
Trimethylbenzene , all isomers	ACGIH	TWA	25 ppm		
	SG OEL	TWA	25 ppm	123 mg/m3	
Cumene	ACGIH	TWA	50 ppm		
	SG OEL	TWA	50 ppm	246 mg/m3	
Naphthalene	ACGIH	TWA	10 ppm		

Safety Data Sheet

	ACGIH	STEL	15 ppm		
	ACGIH	SKIN_DES			Can be absorbed through the skin.
	SG OEL	TWA	10 ppm	52 mg/m ³	
	SG OEL	STEL	15 ppm	79 mg/m ³	

Additional Information : Skin notation means that significant exposure can also occur by absorption of liquid through the skin and of vapour through the eyes or mucous membranes.

Biological Exposure Index (BEI)

Material	Determinant	Sampling Time	BEI	Reference
Ethylbenzene	Sum of mandelic acid and phenylglyoxylic acid in Creatinine in urine	Sampling time: End of shift at end of work week.	0.7 g/g	ACGIH BEL (2011)
	Ethyl benzene in End-exhaled air	Sampling time: Not critical.		ACGIH BEL (2011)
Naphthalene	1-Naphthol, with hydrolysis + 2-Naphthol, with hydrolysis	Sampling time: End of shift.		ACGIH BEL (02 2013)
Xylene	Methylhippuric acids in Creatinine in urine	Sampling time: End of shift.	1.5 g/g	ACGIH BEL (2011)

Appropriate Engineering Controls : The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls

Safety Data Sheet

based on a risk assessment of local circumstances. Appropriate measures include: Use sealed systems as far as possible. Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits. Local exhaust ventilation is recommended. Eye washes and showers for emergency use. Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping. Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation. Firewater monitors and deluge systems are recommended. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle.

- Individual Protection Measures** : Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.
- Respiratory Protection** : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. All respiratory protection equipment and use must be in accordance with local regulations. Select a filter suitable for combined particulate/organic gases and vapors [Type A/Type P boiling point > 65°C (149°F)] meeting EN14387 and EN143.
- Hand Protection** : Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. For continuous

Safety Data Sheet

contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognise that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time may be acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Select gloves tested to a relevant standard (e.g. Europe EN374, US F739). When prolonged or frequent repeated contact occurs, Nitrile gloves may be suitable. (Breakthrough time of > 240 minutes.) For incidental contact/splash protection Neoprene, PVC gloves may be suitable.

- Eye Protection** : Chemical splash goggles (chemical monogoggles). If a local risk assessment deems it so, then chemical splash goggles may not be required and safety glasses may provide adequate eye protection.
- Protective Clothing** : Chemical resistant gloves/gauntlets, boots, and apron (where risk of splashing).
- Thermal Hazards** : Not applicable.
- Monitoring Methods** : Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate. Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory. Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.
National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods <http://www.cdc.gov/niosh/>
Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods <http://www.osha.gov/>
- Environmental Exposure Controls** : Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour. Information on accidental release measures are to be found in section 6. Take appropriate measures to fulfil the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Chapter 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water.

Safety Data Sheet

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Pale straw. Liquid.
Odour	: Hydrocarbon
Odour threshold	: Data not available
pH	: Data not available
Initial Boiling Point and Boiling Range	: 150 - 300 °C / 302 - 572 °F
Freezing Point	: < -47 °C / -53 °F
Flash point	: > 38 °C / 100 °F
Upper / lower Flammability or Explosion limits	: 1 - 6 %(V)
Auto-ignition temperature	: > 220 °C / 428 °F
Vapour pressure	: < 1 hPa at 20 °C / 68 °F
Relative Density	: Data not available
Density	: 775 - 840 kg/m ³ at 15 °C / 59 °F
Water solubility	: Negligible.
Solubility in other solvents	: Data not available
n-octanol/water partition coefficient (log Pow)	: 2 - 6
Dynamic viscosity	: Data not available
Kinematic viscosity	: 1 - 2 mm ² /s at 40 °C / 104 °F
Vapour density (air=1)	: > 5
Electrical conductivity	: Electrical conductivity: 50 - 600 pS/m., The conductivity of this material makes it a static accumulator., A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10 000 pS/m., Whether a liquid is nonconductive or semi-conductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid.
Evaporation rate (nBuAc=1)	: Data not available
Flammability	: Not applicable.

10. STABILITY AND REACTIVITY

Chemical stability	: No hazardous reaction is expected when handled and stored according to provisions.
Possibility of Hazardous	: No hazardous reaction is expected when handled and stored

Safety Data Sheet

Reactions	according to provisions.
Conditions to Avoid	: Avoid heat, sparks, open flames and other ignition sources.
Incompatible Materials	: Strong oxidising agents.
Hazardous Decomposition Products	: Hazardous decomposition products are not expected to form during normal storage. Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.
Sensitivity to Static Discharge	: Yes, in certain circumstances product can ignite due to static electricity.

11. TOXICOLOGICAL INFORMATION

Information on Toxicological effects

Basis for Assessment	: Information given is based on product data, a knowledge of the components and the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
Likely Routes of Exposure	: Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.
Acute Oral Toxicity	: Low toxicity: LD50 > 5000 mg/kg , Rat Aspiration into the lungs may cause chemical pneumonitis which can be fatal.
Acute Dermal Toxicity	: Low toxicity: LD50 >2000 mg/kg , Rabbit
Acute Inhalation Toxicity	: Low toxicity: LC50 >5 mg/l , 4 h, Rat
Skin corrosion/irritation	: Irritating to skin.
Serious eye damage/irritation	: Expected to be slightly irritating.
Respiratory Irritation	: Inhalation of vapours or mists may cause irritation to the respiratory system.
Respiratory or skin sensitisation	: Not expected to be a sensitiser.
Aspiration Hazard	: Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.
Germ cell mutagenicity	: Not considered a mutagenic hazard.
Carcinogenicity	: Not classified as a carcinogen.

Safety Data Sheet

Repeated skin contact has resulted in irritation and skin cancer in animals.

Material	:	Carcinogenicity Classification
Kerosine (petroleum), hydrodesulphurised	:	ACGIH Group A3: Confirmed animal carcinogen with unknown relevance to humans.
Kerosine (petroleum), hydrodesulphurised	:	IARC 3: Not classifiable as to carcinogenicity to humans.
Kerosine (petroleum), hydrodesulphurised	:	GHS / CLP: No carcinogenicity classification
Kerosine	:	ACGIH Group A3: Confirmed animal carcinogen with unknown relevance to humans.
Kerosine	:	IARC 3: Not classifiable as to carcinogenicity to humans.
Kerosine	:	GHS / CLP: No carcinogenicity classification
Kerosine (Fischer Tropsch), Full range, C8-C16 branched and linear alkanes	:	GHS / CLP: No carcinogenicity classification
Naphthalene	:	ACGIH Group A4: Not classifiable as a human carcinogen.
Naphthalene	:	NTP: Reasonably Anticipated to be a Human Carcinogen.
Naphthalene	:	IARC 2B: Possibly carcinogenic to humans.
Naphthalene	:	GHS / CLP: Carcinogenicity Category 2
Xylene	:	ACGIH Group A4: Not classifiable as a human carcinogen.
Xylene	:	IARC 3: Not classifiable as to carcinogenicity to humans.
Xylene	:	GHS / CLP: No carcinogenicity classification
Ethylbenzene	:	IARC 2B: Possibly carcinogenic to humans.
Ethylbenzene	:	GHS / CLP: No carcinogenicity classification
Cumene	:	IARC 2B: Possibly carcinogenic to humans.
Cumene	:	GHS / CLP: No carcinogenicity classification
Trimethylbenzene, all isomers	:	GHS / CLP: No carcinogenicity classification

Reproductive and Developmental Toxicity : Not expected to impair fertility. Not expected to be a developmental toxicant.

Specific target organ toxicity - single exposure : High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.

Specific target organ toxicity - repeated exposure : Kidney: caused kidney effects in male rats which are not considered relevant to humans

Safety Data Sheet

Additional Information : Classifications by other authorities under varying regulatory frameworks may exist.

12. ECOLOGICAL INFORMATION

Basis for Assessment : Fuels are typically made from blending several refinery streams. Ecotoxicological studies have been carried out on a variety of hydrocarbon blends and streams but not those containing additives. Information given is based on a knowledge of the components and the ecotoxicology of similar products.
Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Acute Toxicity : Expected to be toxic: LL/EL/IL50 > 1 <= 10 mg/l (to aquatic organisms) LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract.

Fish : Expected to be toxic: LL/EL/IL50 > 1 <= 10 mg/l

Aquatic crustacea : Toxic: LL/EL/IL50 > 1 <= 10 mg/l

Algae/aquatic plants : Toxic: LL/EL/IL50 > 1 <= 10 mg/l

Microorganisms : Practically non toxic: LL/EL/IL50 > 100 mg/l

Chronic Toxicity

Fish : NOEC/NOEL expected to be > 0.01 - <= 0.1 mg/l (based on modeled data)

Aquatic crustacea : NOEC/NOEL > 0.1 - <=1.0 mg/l

Mobility : Evaporates within a day from water or soil surfaces. Large volumes may penetrate soil and could contaminate groundwater. Contains volatile constituents. Floats on water.

Persistence/degradability : Major constituents are expected to be inherently biodegradable. The volatile constituents will oxidize rapidly by photochemical reactions in air.

Bioaccumulative Potential : Contains constituents with the potential to bioaccumulate. Log Kow > =4

Other Adverse Effects : Films formed on water may affect oxygen transfer and damage organisms.

13. DISPOSAL CONSIDERATIONS

Material Disposal : Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in

Safety Data Sheet

- drains or in water courses. Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination. Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.
- Container Disposal** : Send to drum recoverer or metal reclaimer. Drain container thoroughly. After draining, vent in a safe place away from sparks and fire. Residues may cause an explosion hazard if heated above the flash point. Do not puncture, cut or weld uncleaned drums. Do not pollute the soil, water or environment with the waste container. Comply with any local recovery or waste disposal regulations.
- Local Legislation** : Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be in compliance.

14. TRANSPORT INFORMATION

Land (as per ADR classification): Regulated

Class : 3
Packing group : III
Hazard identification no. : 30
UN number : 1863
Danger label (primary risk) : 3
Proper shipping name : FUEL, AVIATION, TURBINE ENGINE
Environmentally Hazardous : Yes

IMDG

Identification number : UN 1863
Proper shipping name : FUEL, AVIATION, TURBINE ENGINE
Class / Division : 3
Packing group : III
Environmental hazards: Yes

IATA (Country variations may apply)

UN number : 1863
Proper shipping name : Fuel, aviation, turbine engine
Class / Division : 3
Packing group : III

Safety Data Sheet

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution Category	: Not applicable.
Ship Type	: Not applicable.
Product Name	: Not applicable.
Special Precaution	: Not applicable.
Additional Information	: MARPOL Annex 1 rules apply for bulk shipments by sea.

15. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Local Regulations

Workplace Safety and Health Act & Workplace Safety and Health (General Provision) Regulations	: This product is subject to the requirement in the Act/Regulations.
Environmental Protection and Management Act and Environmental Protection and Management (Hazardous Substances) Regulations	: This product is subject to the requirement in the Act/Regulations.
Maritime and Port Authority of Singapore (Dangerous Goods, Petroleum and Explosives) Regulations	: This product is subject to the requirement in the Act/Regulations.
Fire Safety Act and Fire Safety (Petroleum & Flammable Materials) Regulations	: This product is subject to the requirement in the Act/Regulations.

Classification triggering components : Contains kerosine.

16. OTHER INFORMATION

Hazard Statement

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H401	Toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

Additional Information : This document contains important information to ensure the

Safety Data Sheet

safe storage, handling and use of this product. The information in this document should be brought to the attention of the person in your organisation responsible for advising on safety matters.

- SDS Version Number** : 1.0
- SDS Effective Date** : 10.03.2014
- SDS Revisions** : A vertical bar (|) in the left margin indicates an amendment from the previous version.
- Uses and Restrictions** : This product must not be used in applications other than those recommended in Section 1, without first seeking the advice of the supplier.
This product is not to be used as a solvent or cleaning agent; for lighting or brightening fires; as a skin cleanser.
Not to be used as a fuel for automotive vehicles.
Not to be used to prevent waxing in diesel fuel.
- SDS Distribution** : The information in this document should be made available to all who may handle the product.
- Key/Legend to Abbreviations used in this SDS** : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.
- | | |
|------------|--|
| Flam. Liq. | Flammable liquids |
| Skin Corr. | Skin corrosion/irritation |
| Asp. Tox. | Aspiration hazard |
| STOT SE | Specific target organ toxicity - single exposure |
- Key Literature References** : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).
- Disclaimer** : This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.